


Technical Specifications

Product Name	10/100/1000M 30W Two Port PoE Injector
Product Model	PIS2030
Port Description	1x AC Input Port 1x RJ45 Data input port, 1x RJ45 PoE output port
PoE Power Supply	mid-span: 4/5, 7/8 data line pair(default); end-span: 1/2,3/6 spare line pair (can be customized)
Network Medium	1000BASE-TX: 5Cat and more UTP (≤100 meters)
Thermal Protection	>100°C
Performance	Working Rate:10/100/1000Mbps
	Network port protection: meet with IEC61000-4-2(ESD)
	MTBF: 100,000 hours
PoE Standards	IEEE 802.3af/at, PoE+
LEDs Indicator	PoE working status
Power	Total system power: 45W
	PoE port power: 30W (IEEE802.3af/at, PoE+)
	Input Voltage: 120V ~240V AC
Dimensions/Weight	LxWxH: 193.80mm x 117.60mm x 78.49mm (7.63x4.63x3.09 inch) / 4LB / 1.6kg
Working Environment	Operating Temperature: -30°~ 70°C , Storage Temperature: -20°~ 75°C
	Working Humidity: 10%~90%, non-condensing
	Storage Humidity: 10%~95%, non-condensing
Safety & EMC	CE mark, commercial, FCC Part 15 Class B, RoHS UL60950-1, TUV EN60950-1 Approved
Warranty	3-year warranty



RJ45 Conductor Pin#	PSE Pinout		PD Pinout	
	802.3af Mode A	802.3af Mode B/ Passive PoE*	802.3af Mode A	802.3af Mode B/ Passive PoE*
1	Rx, V+	Rx	TX+, V+	TX+
2	Rx, V+	Rx	TX-, V+	TX-
3	Tx, V-	Tx	RX+, V-	RX+
4	Spare	V+		V+
5	Spare	V+		V+
6	Tx, V-	Tx	RX-, V-	RX-
7	Spare	V-		V-
8	Spare	V-		V-

PACKAGE CONTENTS

- PIS2030 (1)
- WECK0001 Waterproof Ethernet Connector Kit (1)
- WPCK0001 Waterproof Power Cord Kit (1)
- User Manual (1)
- 3-Year Warranty Sheet (1)
- MMK0001-XS Pole Mount Kit (1) (Optional)



United States Headquarters 2012 Hartog Drive, CA 95131, U.S.A.
 PHONE +1.408.392.9800 TOLL FREE +1.888.267.4507 FAX +1.408.392.9812
 EMAIL sales@inscapedata.com